



Large-scale pulsed laser deposition (poster)

Pryds, N.; Schou, Jørgen; Linderorth, Søren

Publication date:
2005

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Pryds, N., Schou, J., & Linderorth, S. (2005). *Large-scale pulsed laser deposition (poster)*. Poster session presented at 2005 Annual Meeting of the Danish Optical Society, Roskilde, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Large-scale pulsed laser deposition

Nini Pryds, AFM, Jørgen Schou, OPL, Finn Saxild, AFM and Søren Linderøth, AFM
Risø National Laboratory, DK-4000 Roskilde, Denmark
(AFM, Department of Materials Research; OPL, Department of Optics and Plasma Research)
e-mail: j.schou@risoe.dk

Pulsed laser deposition (PLD) is a unique method for producing thin films of materials of complicated stoichiometry, e.g. metal oxides or metal alloys. Risø National Laboratory has recently established a national facility for making films of large areas. With the present setup uniform films of thickness from a few nanometers up to 1000 nm can be produced on wafers of more than 100 mm of diameter. We have recently also got a grant for a RHEED (Reflected High-Energy Electron Diffraction) instrument which will allow us to produce sandwiches of multilayer films with sharp interfaces at the monolayer level as well as to control the growth rate, film thickness and to determine the lattice spacing.



Plume from a YSZ (yttria-stabilized zirconia) -target irradiated at 248 nm by a KrF-laser in a 0.1-mbar oxygen background gas during deposition of a YSZ-film on a Si wafer. The red triangle above the plume is the hot substrate 85 mm from the target.